

"Express Mail" mailing label no. EE881768336US

Date of Deposit: 30 July 2001

I hereby certify that this paper or fee is being deposited with the United States Postal Service "Express Mail Post Office to Addressee" service under 37 CFR 1.10 on the date indicated above and is addressed to the

Box Patent Application  
Commissioner for Patents  
Washington, D.C. 20231

Jeffrey Slusher

(Typed or printed name of person mailing paper or fee)

Jeffrey Slusher  
Signature of person mailing paper or fee)

Atty. ref: Pos-maetning

**IN THE UNITED STATES PATENT AND TRADEMARK OFFICE**

Attached is a new U.S. Utility Patent Application for:

**TITLE: METHOD AND ARRANGEMENT FOR DETERMINING THE  
POSITION OF AN ELECTROMAGNETIC ACTUATOR**

**INVENTOR(S):**

Name: Johan OLSSON  
Residence: Åmål, Sweden  
Address: Korsbyn 304, 662 91 Åmål, Sweden  
Citizen of: Sweden

**SMALL ENTITY: YES**

# METHOD AND ARRANGEMENT FOR DETERMINING THE POSITION OF AN ELECTROMAGNETIC ACTUATOR

## CROSS-REFERENCE TO RELATED APPLICATIONS

**[0001]** This application claims priority of Swedish Patent Application No. 0002796-1, which was filed on 28 July 2000.

## BACKGROUND OF THE INVENTION

### 5 FIELD OF THE INVENTION

**[0002]** This invention relates to a method and an arrangement for sensing the position of a linear electromagnetic actuator that operates according to the principle of a voice coil.

### DESCRIPTION OF THE RELATED ART

**[0003]** It is known that one can measure the position of an electromagnetic actuator, in which the moving part comprises an iron core arranged so as to be influenced by the magnetic field generated by a stationary coil, by analyzing the inductance of the coil. One example of this method is shown in U.S. Patent 5,172,298. An unavoidable disadvantage of this method is that the relative variation of inductance is low, which causes the absolute accuracy to be low as well. This is clearly a disadvantage if high precision is desired. In US5,172,298 it is also suggested that the coil may be divided into a driving coil and a measuring coil. This is an additional disadvantage, in that this leads to increased complexity.

**[0004]** In order to quickly position, for example, a hard disk pick-up, U.S. Patent  
20 4,937,510, discloses how one may use analog electronics to analyze the electromotive force (emf) that is induced by movement of the coil and therefrom to measure the coil's velocity. The absolute position is in this case controlled according to complicated principles and the measurement of velocity is intended to be used only by a velocity regulator that has a large bandwidth. The same type of velocity feedback has also  
25 been used to regulate the velocity of the coil in a loudspeaker; however, this often involves including a second, dedicated measuring coil in conjunction with the driving

coil. Neither of these two methods is able to produce a value that indicates the absolute position of the actuator.

**[0005]** International Patent Application PCT/SE98/01564 (U.S. Patent 6,246,563, issued 12 June 2001) discloses how yet another actuator principle may be used to

- 5 determine position by measuring variations in inductance, which are derived from the mutual inductance created by the transformer included in the disclosed type of actuator. The principle relies, however, on a complex structure with respect to both the driving of the actuator and to analysis of the position of the actuator, which in certain applications is undesirable.

## 10 SUMMARY OF THE INVENTION

**[0006]** The object of the invention is to solve the above-mentioned problems in order to achieve a rapid and accurate measurement of the position of the moving coil in a linear actuator based on the principle of a voice coil. This object is achieved by driving and measuring the position of an actuator, which has a gap that is magnetized by a permanent magnet, and in which gap a voice coil is arranged to move between two end positions, where the amount of core material that is surrounded by the voice coil varies as a function of position. The voice coil is connected to a controllable current source, so that the average current of the voice coil can be controlled. This in turn controls the actuator force. An alternating current component is then also included in the control current, by means of which the phase shift of the circuit can be measured. This phase shift then provides a measure of the position of the voice coil relative to the core material. One advantage of the invention is that it eliminates the need for end point breaker switches.

- [0007]** The invention makes possible the use of the voice coil principle in new  
25 applications. Characteristic of the principle of a voice coil is that it forms a quick, bidirectional, highly dynamic force source. When this principle is complemented with a simple and exact method for measuring position, new areas of application are created.

**[0008]** The position information that the invention generates may be used in any number of different contexts. One example is that actual position information can be

used in any system that regulates the position of the actuator -- regulators require some information about instantaneous position and this invention provides such information. For example, the invention may be used to generate position-feedback information in a position-regulated system. Yet another example are diagnostic functions for checking and analyzing the operation of the actuator itself.

**[0009]** The voice coil is driven by a current source that can in part control the average current through the voice coil and in part create an AC component. The average current provides for control of the force that the voice coil is to develop and the AC component provides an opportunity to analyze the inductance in the voice coil. The inductance of the voice coil can be caused to vary greatly as a function of position by allowing part of the voice coil to extend outside of the inner core when the voice coil is in its outermost position.

**[0010]** In the preferred embodiment of the invention, the current source comprises one or more switching elements that apply voltage to the voice coil in such a way that the instantaneous current value through the voice coil oscillates between two controllable limiting values. The frequency of oscillation then becomes a measure of the position of the voice coil. A present position value of the voice coil is sensed and is coupled to a feedback position regulator that controls the average current through the voice coil.

**[0011]** In one optimized embodiment of the invention, the temperature in the voice coil is measured, from which a compensation factor is derived and used to compensate the measurement error that is caused by temperature changes in the voice coil.

#### BRIEF DESCRIPTION OF THE DRAWINGS

**[0012]** Figure 1 shows a cross-section of an actuator that operates according to the voice coil principle.

**[0013]** Figure 2 is a circuit diagram that exemplifies the driving electronics used in the preferred embodiment of the invention.

**[0014]** Figure 3 is a coil current vs. time, position vs. time, and control signal vs. time diagram for an actuator during movement from its innermost to its outermost position.

## DETAILED DESCRIPTION

[0015] Figure 1 illustrates a cross-section of a cylindrical linear actuator that has a permanent magnet 2, an iron core 1, an outer ring 5 and a voice coil 3, which has an actuator arm portion 4 and is driven by a current source. The current source is included  
5 as part of drive and measurement circuitry 7, which is connected via conventional conductors 8 to the windings of the coil. An air gap 6 separates the voice coil 3 from the core 1. The voice coil 3 is able to move laterally (indicated by a double arrow), viewed as in the figure. When the voice coil 3 moves outward in the direction away from the iron core 1, its inductance will decrease correspondingly because the portion of the  
10 iron core 1 that is surrounded by the coil decreases.

[0016] If the relationship between the length of the air gap 6, of the stroke length of the coil, and the length of the coil (that is, the extent of its windings) is in the proportion 1:1:2, then the variation in coil inductance will approach 50%. Such a large variation provides good conditions for measuring inductance variations and therefrom determining the position of the coil with a high degree of accuracy. There is a trade-off between stroke length and efficiency, because an increased stroke length leads to an increased proportion of the coil that is no longer located in the air gap 6 and thus does not develop force to the same extent. A certain force will be generated because the magnetic flux density decreases gradually with increasing distance from the air gap 6.

[0017] Figure 2 illustrates one embodiment of the method according to the invention, which is also included as part of the drive and measurement circuitry 7. In this embodiment, the voice coil 3 is driven by either a positive or a negative voltage (+Vs and -Vs, respectively) via two switching elements, in particular, transistors Qa, Qb, which are preferably provided with conventional respective freewheel diodes Da, Db.  
25 Regulation of the force occurs because the circuit oscillates between two current levels, which are represented as the Control signal in Figure 3. The two current levels are determined by a comparator 14 and a hysteresis arrangement 13. In the illustrated preferred embodiment, the hysteresis arrangement 13 is formed by a parallel-connected pair 13 of oppositely biased diodes, which connect the output of a feedback  
30 regulator 11 with one input of the comparator 14.

[0018] The switching transistors Qa, Qb are driven by means of an inverter 18, together with transistor-driving stages 16a, 16b, which ensure that either the one or the other of the switching transistors Qa, Qb is conductive. The coil 3 is preferably connected to a system ground via a resistive shunt Rshunt. An input (preferably, the positive input, to preserve polarity) of an amplifier 15 is connected between the coil 3 and ground; in Figure 3, this connection point is illustrated as point P1, which is also the point at which the coil current  $I_{coil}$  is sensed. The amplifier 15 converts the coil current  $I_{coil}$  into a corresponding voltage value and amplifies this voltage value -- a conventional resistive net is shown in Figure 2 connected to the amplifier 15 in order to scale the amplifier output as needed for subsequent comparison. The amplifier 15 is preferably of the type that has a very high input impedance, such as a standard operational amplifier, so that any loss of current through the coil caused by the amplifier will be negligible.

[0019] When the amplifier 15 output voltage exceeds the level that is set by the output voltage of the position regulator 11 plus the hysteresis of the comparator 14, then the positive driving transistor Qa is shut off and the negative driving transistor Qb is turned on; when the output voltage is less than the level from the position regulator minus the hysteresis of the comparator, then the negative transistor Qb is turned off and the positive transistor Qa is turned on.

[0020] The frequency with which the transistors Qa, Qb are switched depends in part on the hysteresis of the comparator 14, which is set by the diode pair 13 and is constant, and in part on the time derivative of the current  $I_{coil}$  through the voice coil 3. The current  $I_{coil}$  in turn is a function of the instantaneous coil inductance, which in turn depends on the position of the coil relative to the core 1. The switching frequency is thus a function of the position of the coil. This is illustrated in Figure 3, which shows the position lying farther from an origin position with increasing frequency of oscillation of the coil current  $I_{coil}$ .

[0021] The output of the comparator 14, which is indicated at point P2 in Figure 2 forms the Control signal illustrated in Figure 3. In addition to controlling the switching transistors Qa, Qb, the control signal is also connected as the input to a frequency-to-



eliminated by adjusting the relationships between, for example, driving voltage, conductor diameter, and the number of windings in the voice coil.

**[0026]** The exemplifying embodiment above is based on an inductance-dependent oscillation where the inductance is changed by the position of the voice coil. Other solutions are also possible, however, such as allowing the actuator force to be controlled by an H-bridge, where the pulse ratio applied to the coil controls the delivered force, but with a constant frequency. The time derivative of the coil current can then be sampled, using known circuitry, whenever the H-bridge is shut off and the energy stored in the voice coil drains away. The time derivative of the current is then a measure of the inductance of the coil.

**[0027]** In yet another possible alternative embodiment of the invention, the current of the voice coil is controlled by an applied DC voltage, which will control the amount of force generated by the actuator. A sinusoidal alternating voltage having a constant amplitude may then be superimposed on the driving voltage signal. The phase shift between the alternating voltage and the alternating current that is thereby formed through the voice coil can then be measured and will indicate the position of the coil.

**[0028]** Note that in all embodiments of the invention described above, the actuator itself is used as part of the arrangement that measures the position of the actuator; indeed, other than the measurement circuitry (for example, as shown in Figure 2) no additional components are needed at all. In particular, no special or additional mechanical parts, such as secondary coils, are required. Moreover, it is not necessary to partition the coil, that is, divide the coil windings into separately controlled or tapped portions.

**[0029]** Any application of current to the windings of the coil 3, for example, as a result of the position set-point signal, will of course influence the position of the coil. This means, however, that even the alternating signal  $I_{coil}$  will cause coil movement, in particular, an oscillation. In order to keep the effect of such oscillation to within acceptable, predetermined limits, lowest frequency of  $I_{coil}$  should be set above the upper limit of the mechanical bandwidth of the coil 3 and the actuator arm 4.

Depending on the mass properties of the coil (including windings) and arm, it may also



be necessary or at least preferable to ensure that the range of frequencies of Icoil does not include any harmonic of the resonant frequency of the moving mass. The mass properties of the moving parts of the actuator and the necessary frequency range of Icoil and thus of the control signal may be determined for each implementation of the invention using conventional experimental and analytical methods.

**[0030]** If a given application has stringent demands for absolute position measurement, then variations in coil resistivity caused by changes in temperature will negatively influence the measurement results. It is in such case possible to measure the resistance by using known circuitry (which may then be included in the drive and measurement circuitry 7) to calculate the ratio of the average values of current and voltage through the voice coil, which can then in turn be used to correct the actual position value. It would also be possible to provide the voice coil with a temperature sensor (which would be connected to the drive and measurement circuitry 7 in any known way) for the same purpose, in order to sense temperature directly and compensate for resistivity changes based on the sensed temperature. The amount of compensation needed can be determined through normal calibration techniques and theoretical calculations.

**[0031]** It would thus be possible according to the invention to arrange the magnetic circuit differently than shown in Figure 1. For example, the component permanent magnets and details of the core can be varied with respect to number, shape and placement. Other embodiments are also possible within the scope of the invention, in which a single permanent magnet is used to drive several different air gaps, each having a corresponding voice coil. Moreover, the electronics that are used for sensing, for example, the phase shift may be implemented in any known manner without departing from the idea of the invention. It is also not necessary for the cross section of the actuator to be circular, as is shown in the example above.